



# KRAUS SINGLE HANDLE PULL DOWN KITCHEN FAUCET COMMERCIAL STYLE PRE-RINSE

IN STOCK



Finish



Stainless Steel



Chrome

## DESCRIPTION

The best kitchen ideas start with great design. Kraus commercial style faucets feature a unique industrial aesthetic that creates a dramatic look with contemporary appeal. Each best selling faucet is constructed with certified lead-free brass and top-quality components, including a high performance / low flow Neoperl aerator and a precision Kerox ceramic cartridge for reliable drip-free use. With a choice of flawless commercial grade stainless steel or chrome finish, this faucet matches many popular fixtures and appliances, resulting in a beautifully coordinated look for your kitchen. For flexible functionality, this ultra modern faucet has a pull-down spray head and side pot filler. Single-hole mounting allows the faucet to integrate seamlessly with your sink. For easy installation, all mounting hardware is provided. Experience Kraus Quality and bring your best kitchen ideas to life.

## Benefits & Features

- Lead-Free Brass Construction w/ Superior Rust-Resistant Finish
- LiteTouch Single-Lever Flow Control
- Heavy-Duty Commercial-Style Spring Design
- Integrated Two-Way Diverter for Smooth Flow Control
- Powerful Pre-Rinse Spray
- Spout Swivels for Complete Sink Access
- Easy-Clean Rubber Nozzles Prevent Hard Water Build-Up
- Kerox Ceramic Cartridge (tested w/ 500,000 cycles)
- High Performance / Low Flow Neoperl Aerator
- Limited Lifetime Warranty
- Certified and Listed by cUPC , UPC, NSF/ANSI Standard certified by IAPMO, ANSI, AB1953, CALGreen, FTC, DOE, CEC, MASS, CSA, IAPMO, SCC, and ADA
- Faucet Height: 29"-32"
- Spout Height: 11.5"
- Spout Reach: 8.5"
- Spout Swivel: 360° (Degrees)
- Flow Rate: 1.8 GPM
- Faucet Hole Size Requirement: 1.375"
- Number of Holes Required: 1
- Maximum Deck Thickness: 1.75"

## ADDITIONAL INFORMATION

<b>COLLECTION NAME</b>	Premium Kitchen Faucet
<b>AERATOR CLEARANCE (INCHES)</b>	N/A
<b>MATERIAL</b>	Solid Brass
<b>MOUNT TYPE</b>	Deck Mount
<b>NUMBER OF SPRAY SETTINGS</b>	1
<b>FAUCET TYPE</b>	Pull Down
<b>WIDTH</b>	2.20
<b>FAUCET HEIGHT</b>	32.00
<b>SPOUT REACH</b>	8.50
<b>SPOUT HEIGHT</b>	11.50
<b>FAUCET HOLES / HOLES REQUIRED</b>	1.00
<b>FLOW RATE (GPM)</b>	1.80
<b>HOSE LENGHT</b>	31.50
<b>HEIGHT</b>	32.00
<b>FAUCET CERTIFICATIONS</b>	AB 1953, cUPC, NSF/ANSI Standard 61 certified by IAPMO, CAL Green, DOE, NSF/ANSI Standard 372 certified by IAPMO, FTC, CEC, MASS
<b>WARRANTY</b>	Limited Lifetime
<b>HANDLE CLEARANCE</b>	0.00
<b>MAX DECK THICKNESS</b>	1.75
<b>MOUNTING TYPE</b>	N/A