



## Portable Heat Pump Air Conditioners

# 20ACH 1811

<b>Cooling Capacity</b>	@ARI 80°F-67°F at 52% Relative Humidity	1.5 Ton - 16,800
<b>Heating Capacity</b>	@ARI 70°F-60°F at 60% Relative Humidity	15,600
<b>Dimensions</b>	Width (Inches)	24
	Depth (Inches)	30
	Height (Inches)	45.5
	Weight (Pounds)	260
	Shipping Weight	285
	Shipping Volume (cubic feet)	28
<b>Electrical Characteristics</b>	Power Supply (Volts)	115/1
	Current Consumption	14.1
	Cooling Watts	1670
	In rush current (Amps)	100.5
	NEMA Plug Configuration	5-20p
	EER	10.0
	Min-max Voltage	105-125
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
<b>Compressor Characteristics</b>	Compressor HP	1.5
	Compressor RLA	12.3
	Compressor LRA	63
<b>Evaporator</b>	Evap (CFM)	600
	Evap Motor HP	1/8
	Evap Motor Watts	210
<b>Condenser Characteristics</b>	Condenser CFM	930
	Condenser Motor HP	1/8
	Condenser Motor Watts	280
<b>Miscellaneous Features</b>	Condensate	5 gal. tank
	Sound Level	60
	R-410A Charge Oz.	40



## Portable Heat Pump Air Conditioners

# 20ACH 1811

**Power Supply** 115 volts 60 hertz 1 phase 14.1 amperes

**Width** 24 inches

**Depth** 30 inches

**Height** 45.5 inches

**Weight** (net/shipping) lbs 260/285

All models are backed by a 12-month warranty with 60 months for the compressor.

