

CK, CKT, & CK Trend Technical Data

Technical Data



Certified to ANSI/UL Std. 2021
Conforms to CAN/CSA Std. 22.2 No. 46



Model	CK 15 E	CKT 15 E	CK 20 E		CKT 20 E		CK 150-1 Trend	CK 200-2 Trend		
Item number	074058	230345	074057		230346		236304	236305		
Voltage	120 v	120 v	240 v or 208 v		240 v or 208 v		120 v	240 v or 208 v		
Wattage	1500 w	1500 w	2000 w	1500 w	2000 w	1500 w	1500 w	2000 w	1800 w	
Amperage	12.5 A	12.5 A	8.3 A	7.2 A	8.3 A	7.2 A	12.5 A	8.3 A	8.7 A	
Rated output Btu/hr	5118	5118	6824	5118	6824	5118	5118	6824	6142	
Air volume	106 CFM	106 CFM	106 CFM		106 CFM		70.6 CFM	70.6 CFM		
Recommended circuit breaker size ¹	15 A	15 A	15 A		15 A		15 A	15 A		
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG		14 AWG	14 AWG		
Timer	no	yes	no		yes		N/A	N/A		
Room size estimate	150 sq. ft.	150 sq. ft.	200 sq. ft.		200 sq. ft.		150 sq. ft.	200 sq. ft.		
Heating element	nichrome wire						ceramic positive temperature coefficient (PTC)			
Thermostat & high limit	bimetal type						bimetal type			
Motor	18 w shaded pole						20 w shaded pole			
Blower	galvanized steel, squirrel cage type						glass-reinforced polycarbonate, radial type			
Dimensions	18 ¹ / ₈ "/460 mm H x 13 ³ / ₁₆ "/335 mm W x 4 ¹³ / ₁₆ "/123 mm D						15 ³ / ₄ "/400 mm H x 10 ⁷ / ₈ "/275 mm W x 5 ¹ / ₈ "/131 mm D			
Weight	8.0 lb / 4.4 kg						5.5 lb / 2.5 kg			
Temperature range	41°F – 86°F / 5°C – 30°C						45 – 95 °F / 7 – 35 °C			
Frost protection setting	45°F / 7°C						45°F / 7°C			
Operating noise	49.7 dB(a)						49.0 dB(a)			

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary.