


PTAC PDH12K3SG

Cooling BTU: **11800/11600**
Heating BTU: **10600/10400**
EER: **11.6/11.6**

Volts: **230/208**



Unit Dimensions

Height: **16"**
Width: **42"**
Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
Front Cover Width: **42"**
Front Cover Depth: **7 3/4"**
Cut-Out Height: **16 1/4"**
Cut-Out Width: **42 1/4"**
Dimensions With Package: **21 1/2"**
Net Weight: **122 lbs**
Shipping Weight: **141 lbs**

Detailed Electrical Information



Voltage: **230/208**
Volt Range: **253-187**
Cooling Amps: **4.9/5.1**
Cooling Watts: **1015/1000**
Reverse Heating Amps: **4.2/4.7**
Reverse Heating Watts: **910/895**
Compressor LRA: **21.5**
Compressor RLA: **4.7**

Additional Performance Specs

Air Circulation: **300 CFM**
COP: **3.4/3.4**
Moisture Removal: **2.7 pints per hour**
Indoor CFM High: **400**
Indoor CFM Low: **390**
Sensible Heat Ratio: **0.75**
Vent CFM: **75**
R-410A Charge: **36 oz**
Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645