

## FFEC3025U S/B

### BUILT-IN COOKTOP 30" ELECTRIC



#### PRODUCT DIMENSIONS

Width	30-3/8"
Depth	21-3/8"
Height	2-5/8"

#### MORE EASY-TO-USE FEATURES

##### Ready-Select® Controls

Easily control your cooking temperature with our easy-to-use controls.

##### Hot Surface Indicator

Alerts you when your cooktop may be too warm to touch.

##### Approved Over Frigidaire® Electric Wall Ovens

Cooktops are approved for installation above any of our Single Electric Wall Ovens.

#### AVAILABLE COLORS



Stainless Black

ELEMENTS	SIZE	WATTS
Right Front	Electric 6" / 9"	1,600 / 3,000
Right Rear	Electric 6"	1,200
Left Front	Electric 6"	1,200
Left Rear	Electric 9"	2,500

#### SIGNATURE FEATURES

##### Quick Boil Element

Get meals on the table faster with our powerful 3,000W Quick Boil element.

##### SpaceWise® Expandable Element

Flexible element expands to accommodate various sizes of cookware.

##### Frigidaire® Fit Promise

We promise that your new 30" Frigidaire® brand cooktop will fit your existing countertop cutout of the same width and configuration, or we will reimburse you for countertop modification costs up to \$100.

##### Ceramic Glass Cooktop

For a more beautiful cooktop that's easy to clean.

# FFEC3025U S/B BUILT-IN COOKTOP

30" ELECTRIC

FRIGIDAIRE

## FEATURES

Controls	Ready-Select*
Surface Type	Black Ceramic Glass
Right Front Element (Watts)	6" / 9" - 1,600 / 3,000
Right Rear Element (Watts)	6" - 1,200
Left Front Element (Watts)	6" - 1,200
Left Rear Element (Watts)	9" - 2,500
Hot Surface Indicator	Yes
Control Location	Right
Knob Type	Plastic

## SPECIFICATIONS

Power Supply Connection Location	Right Rear
Voltage Rating	240V / 208V / 60Hz
Connected Load (kW Rating) @ 240 / 208 Volts	7.9 / 5.9
Amps @ 240 / 208 Volts	32.9 / 28.4
Minimum Circuit Required (Amps)	40
Approved for Electric Single Wall Oven Combination Installation <sup>1</sup>	Yes
Shipping Weight (Approx.)	49 Lbs.

<sup>1</sup>Cooktops are approved for installation above any of our Electric Single Wall Ovens.


## PRODUCT DIMENSIONS

A - Width	30-3/8"
B - Depth	21-3/8"
C - Height	2-5/8"

## CUTOUT DIMENSIONS

Width (Min. - Max.)	28-1/2" - 29-7/8"
Depth (Min. - Max.)	19-5/8" - 20-1/2"
Height (Min.)*	5"

\*Includes clearance needed beneath cooktop to allow for armored cable and installation of junction box on back wall.  
Granite Countertop Installation Kit available.



**Note:** For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com](http://frigidaire.com) / [frigidaire.ca](http://frigidaire.ca).  
Specifications subject to change. Accessories information available on the web at [frigidaire.com](http://frigidaire.com) / [frigidaire.ca](http://frigidaire.ca)

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • [frigidaire.com](http://frigidaire.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [frigidaire.ca](http://frigidaire.ca)

FFEC3025U 11/18  
© 2018 Electrolux Home Products, Inc.

PRODUCT DIMENSIONS

A - Width	30-3/8"
B - Depth	21-3/8"
C - Height	2-5/8"

CUTOUT DIMENSIONS


D - Width (Min.)	28-1/2"
(Max.)	29-7/8"
E - Depth (Min.)	19-5/8"
(Max.)	20-1/2"
F - Height (Min.)*	5"

REQUIRED CLEARANCES

G - (Min.)	2"
H - (Min.)	7-1/2"
I - (Min.)	7-1/2"
J - (Min.)	2-1/2"
K - Cabinet Opening Width (Min.)	30-3/8"

UTILITY CONNECTION LOCATIONS

Power Supply	Right Rear
--------------	------------



INSTALLATION SPECIFICATIONS

- Product Shipping Weight (approx.) - 49 Lbs.
- Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.
- Connected Load (kW Rating) @ 240/208 Volts = 7.9/5.9kW
- Amps @ 240/208 Volts = 32.9/28.4 Amps
- Recommended Circuit Breaker - 30 Amps
- Always consult local and national electric codes.
- Cooktop cutout height includes clearance needed beneath cooktop to allow for armored cable and installation of junction box on back wall. Position center of junction box 10" inward from right side of cooktop cutout, and 12" down from underside of countertop.
- Overhead cabinetry should not exceed a 13" maximum depth.
- Absolute minimum horizontal distance between overhead cabinets installed to either side of appliance must be no less than 30-3/8".
- Allow 30" minimum clearance between top of cooktop platform and bottom of unprotected wood or metal overhead cabinet; or 24" minimum clearance

when bottom of wood or metal overhead cabinet is protected by not less than 1/8" flame-retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper.

- Allow 2" minimum clearance between rear edge of cutout and nearest combustible surface (or backsplash) above countertop.
- Allow 7-1/2" minimum required clearance from left edge of cooktop to nearest combustible wall and 7-1/2" minimum from right edge of cooktop to nearest combustible wall.
- Installation of drawer beneath cooktop requires 4" minimum clearance beneath countertop surface, and assured clearance for electrical installation.
- To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets.

OPTIONAL ACCESSORIES

- Granite Countertop Installation Kit - (PN # 903061-9010).



FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidair.com  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidair.ca

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidair.com / frigidair.ca. Specifications subject to change. Accessories information available on the web at frigidair.com / frigidair.ca

FFEC3025U 11/18  
© 2018 Electrolux Home Products, Inc.