

TWI180 WP Eco&Steam WiFiConn.

T1 Heat-pump tumble dryer
with WiFiConn@ct, FragranceDos, and SteamFinish.



- Ventless, up to 60% energy savings with heat-pump technology
- Quick alternative to ironing with steam smoothing - SteamFinish
- Precision drying of all textiles – Perfect Dry
- Fragrant laundry just the way you like it – FragranceDos
- ENERGY STAR® qualified

EAN: 4002515837467 / material number: 10666300

Construction type	
Stackable	•
Side-by-Side	•
Slot-in	•
Door hinging	right
Construction type	
Heat-pump dryer	•
Design	
Appliance color	Lotus white
Control panel color	Lotus white
Door design	Lotus white
Rotary selector color	Lotus White / Chrome ring
Fascia panel version	5° incline
Control type	Rotary selector
Control panel	DirectSensor white, 1 line
Drying results	
PerfectDry	•
FragranceDos	•
Intelligent drum reversal	•
Gentle laundry care	
Honeycomb drum	•
Load in lbs. (kg)	18 (8.0)
Control panel	
Delay start up to 24 h	•
Countdown indicator	•
Program sequence indicator	•
Drum lighting	LED
MultiLingua	•
Condensed water container	•
Integrated condensed water drainage	•
Efficiency and sustainability	
EcoFeedback function	•
EcoDry technology	•
Maintenance-free heat exchanger	•
ProfiEco motor	•

TWI180 WP Eco&Steam WiFiConn.

T1 Heat-pump tumble dryer
with WiFiConn@ct, FragranceDos, and SteamFinish.



Drying programs	
Delicates	•
Express	•
Outdoor	•
Proofing	•
Normal	•
Wrinkle-free	•
Smoothing	•
Woolens/Silks	•
Dress Shirts	•
Time Dry	•
Denims	•
Table Linens/Drapes	•
Bed Linen	•
Cold Air	•
Basket	•
Sportswear	•
Settings	•
Soft Steam	•
Drying options	
Anti-crease action	•
Gentle tumble	•
Freshen up	•
Acoustic signal	•
Appliance networking	
WiFiConn@ct	•
Quality	
Soft ribs	•
Safety	
Lock code	•
Empty out container" indicator	•
Clean filter" indication	•
Optical interface	•
Technical data	
Dimensions (width) in in.(mm)	23 1/2 (596)
Dimensions (height) in in.(mm)	33 1/2 (850)
Dimensions (depth) in in.(mm)	25 3/8 (643)
Depth with door open in in.(mm)	42 1/2 (1,077)
Weight in lbs. (kg)	135 (61)
Total connected load in kW	1.0
Fuse rating in A	15
Length of supply lead in feet (ft.)	6 (2)
Type of coolant	R134a
Standard accessories	
Fragrance flacon	•