



24" C-SERIES
Beverage Center



ecofriendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
HC24BB-4-1R/L	Indoor C-Series Beverage Center Solid Stainless Steel Door
HC24BB-4-2R/L	Indoor C-Series Beverage Center Solid Panel Ready Door
HC24BB-4-3R/L	Indoor C-Series Beverage Center Stainless Steel Glass Door
HC24BB-4-4R/L	Indoor C-Series Beverage Center Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- 800 BTU/hr capacity delivers commercial grade cooling performance
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Wine and refrigerator shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time

Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 62 cans and 16 bottles of wine



24" C-SERIES
Beverage Center

MODEL NUMBERS		HC24BB
MODEL DESCRIPTION		24" Indoor Beverage Center
ATTRIBUTES		
Perlick Anti-Condensation System		NO
Energy Star Certified		YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		195 lbs (88.45 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
REFRIGERATION SPECIFICATIONS	Lighting Type	LED
	Refrigerant	R600a (50g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	800 BTU/hr
FRONT VENTED		Yes
PLUMBING		None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736	Caster Kit for HP24/HC24/HA24 models
RS-24-24D	Divider Shelf for HP24/HC24/HA24 models

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



24" C-SERIES
Beverage Center

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HC24BB-4-1L	HC24BB4C-00-SLS0B	Left	No
HC24BB-4-1R	HC24BB4C-00-SRS0B	Right	No
HC24BB-4-2L	HC24BB4C-00-PL00B	Left	No
HC24BB-4-2R	HC24BB4C-00-PR00B	Right	No
HC24BB-4-3L	HC24BB4C-00-TLS0B	Left	No
HC24BB-4-3R	HC24BB4C-00-TRS0B	Right	No
HC24BB-4-4L	HC24BB4C-00-RL00B	Left	No
HC24BB-4-4R	HC24BB4C-00-RR00B	Right	No
HC24BB-4-1LL	HC24BB4C-00-SLSLB	Left	Yes
HC24BB-4-1RL	HC24BB4C-00-SRSLB	Right	Yes
HC24BB-4-2LL	HC24BB4C-00-PL0LB	Left	Yes
HC24BB-4-2RL	HC24BB4C-00-PR0LB	Right	Yes
HC24BB-4-3LL	HC24BB4C-00-TLSLB	Left	Yes
HC24BB-4-3RL	HC24BB4C-00-TRSLB	Right	Yes
HC24BB-4-4LL	HC24BB4C-00-RL0LB	Left	Yes
HC24BB-4-4RL	HC24BB4C-00-RR0LB	Right	Yes



24" C-SERIES
Beverage Center

