

G 7591 SCVi AutoDos  
Fully integrated ADA dishwasher  
with Automatic Dispensing thanks to AutoDos with integrated PowerDisk.



- ExtraComfort Baskets w/3D MultiFlex Tray adjusts for more volume
- [Miele@home](mailto:Miele@home) w/ AutoStart, remotely program your dishwasher
- Automatic door opening after two knocks – Knock2open
- Perfect illumination for easy loading – BrilliantLight
- All safely loaded where needed – Maxi comfort basket design

EAN: 4002516261551 / Material number: 11388260 / Old Material Number: 21759162USA

<b>Construction type</b>	
Fully integrated dishwashers	•
24 inch dishwasher	•
<b>Design</b>	
Fascia color	Clean Touch Steel/Obsidian Black
Fascia panel version	Fully integrated fascia
Control type	Softkeys
Control panel	1-line text display
Display color	White
MultiLingua	•
<b>Convenience</b>	
Networking with Miele@home	•
Automatic dispensing with PowerDisk	•
Knock2open	•
Door closing aid	AutoClose
LED Lighting	•
Operating noise dB(A) re 1 pW	40
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	optical and acoustic
Display language selection	•
<b>Efficiency and sustainability</b>	
EcoFeedback	•
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
ENERGY STAR® Most Efficient	•
<b>Gentle on dishware/glass</b>	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Active condensation drying	•
Perfect GlassCare	•
<b>Dishwashing programs</b>	
QuickIntenseWash	•
Economy	•
Normal	•
SensorWash	•
Pots & Pans	•
IntenseWash	•
China & Crystal	•
SaniWash	•
Energy Saver	•
Extra Quiet	•
Glasses – No Rinse Aid	•
Appliance care	•
Rinse & Hold	•

## G 7591 SCVi AutoDos

Fully integrated ADA dishwasher

with Automatic Dispensing thanks to AutoDos with integrated PowerDisk.



EAN: 4002516261551 / Material number: 11388260 / Old Material Number: 21759162USA

<b>Rinse options</b>	
AutoDos	•
IntenseZone	•
Express	•
Extra Clean	•
Extra dry	•
<b>Basket design</b>	
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	4
FlexCare cup rack	2
Basket design	MaxiComfort
<b>Safety</b>	
Waterproof system	•
Check filter saturation indicator	•
Child Safety lock	•
<b>Technical data</b>	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	32 1/8 (815)
Niche height max in in.(mm)	34 3/4 (880)
Niche depth in in.(mm)	21 3/4 (550)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	32 1/8 (815)
Appliance depth in in.(mm)	21 3/4 (550)
Appliance depth with door open in in.(cm)	45 7/8 (116.5)
Net weight in lbs. (kg)	106 (48.0)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)
Min. front panel weight in kg	3.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	8.0
[can be retrofitted by Service to max.]	17.0
Replacing bulbs	Customer Service
<b>Available display languages</b>	
Available display languages via MultiLingua	deutsch, english, español, français, português,