

# Gas Range, 48", 8 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- Made from quality materials and real stainless steel

## DIMENSIONS

Height	35 <sup>3</sup> / <sub>4</sub> - 36 <sup>3</sup> / <sub>4</sub> "
Width	47 <sup>7</sup> / <sub>8</sub> "
Depth	29 <sup>1</sup> / <sub>8</sub> "

## FEATURES & BENEFITS

### Generous capacity

Featuring a generous total capacity of 7.7 cu ft, with enough room to fit a 32 lb turkey, or to cook several dishes at once.

## SPECIFICATIONS

### Accessories

Square handle option	AH-R48
----------------------	--------

### Capacity

Shelf positions	5
Total capacity	7.7 cu ft
Usable capacity	5.6 cu ft

### Cleaning

Easy clean porcelain basepan	•
------------------------------	---

### Controls

Metal illuminated dials	•
Star K Certification	•
Titanium coated, illuminated	•

### Gas requirements

Fitting and pipe	½ NPT, min. ⅝" flex line
Gas requirements	LPG
Supply Pressure (LPG)	11" to 14" W.C

### Main oven features

Broil pan	•
Capacity total (AHAM)	5.3 cu ft
Capacity usable (AHAM)	3.9 cu ft
Electronic oven control	•
Full extension telescopic racks	2
Infrared Broiler	•
Internal Light	•
Shelf positions	5

### Main oven functions

Bake	•
Broil	•
Convection bake	•
Number of main oven	4
Slow cook	•

### Oven performance

Main oven - Bake power	21,500 BTU
Main oven - Broil power	19,000 BTU
Secondary oven - Bake power	14,000 BTU

### Power requirements

Amperage	15A
Supply frequency	60Hz
Supply voltage	120V

**Product dimensions**

Depth	29 1/8"
Height	35 3/4" - 36 3/4"
Width	47 7/8"

**Rangetop features**

Sealed Dual Flow Burners™	8
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim

**Rangetop Performance**

Back centre	13,000 BTU
Front centre	15,000 BTU
Left front zone rating	17,000 BTU
Left rear zone rating	13,000 BTU
Max burner power	17,000 BTU
Right front zone rating	17,000 BTU
Right rear zone rating	13,000 BTU
Total cooktop power	116,000 BTU

**Recommended back guards and ventilation**

Combustible situation	BGRV3-3048H
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48" Professional)

**Safety**

ADA compliant	•
Full extension telescopic	•

**Secondary oven features**

3/4 Extension racks	2
Capacity total (AHAM)	2.4 cu ft
Capacity usable (AHAM)	1.7 cu ft
Electronic oven control	•
Internal light	•
Shelf positions	5

**Secondary oven functions**

Bake	•
Convection bake	•
Number of secondary oven	4
Proof	•
Slow cook	•

**Warranty**

Parts and labor	2 years
-----------------	---------

SKU	81995
-----	-------

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

**Other product downloads available at fisherpaykel.com**

- [↓](#) User Guide
- [↓](#) Service & Warranty Booklet
- [↓](#) Installation Guide



**A PEACE OF MIND SALE**

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 W www.fisherpaykel.com