



**24" C-SERIES**  
*Wine Reserve*



**eco**friendly  
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



**Glass Door Model**



**Solid Door Model**

MODELS	DESCRIPTION
<b>HC24WB-4-1R/L</b>	Indoor C-Series Wine Reserve Solid Stainless Steel Door
<b>HC24WB-4-2R/L</b>	Indoor C-Series Wine Reserve Solid Panel Ready Door
<b>HC24WB-4-3R/L</b>	Indoor C-Series Wine Reserve Stainless Steel Glass Door
<b>HC24WB-4-4R/L</b>	Indoor C-Series Wine Reserve Panel Ready Glass Door

### KEY PRODUCT FEATURES AND BENEFITS

- 800 BTU/hr capacity delivers commercial grade cooling performance
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Wine shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time

### Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 45 bottles of wine



**24" C-SERIES**  
*Wine Reserve*

MODEL NUMBERS		HC24WB
MODEL DESCRIPTION		24" Indoor Wine Reserve
ATTRIBUTES		
Perlick Anti-Condensation System		NO
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		195 lbs (88.45 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (50g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	45° (7.2°) - 42° (18.3°) <b>Factory Set Point 36° (2.2°)</b>
	Heat Rejection (at 75°F)	450 BTU/hr
	Pull Down Capacity	800 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

*Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.*

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736	Caster Kit for HP24/HC24/HA24 models
67115-24	Wood Faces for Wine Shelf (7/pk)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit [perlick.com](http://perlick.com).



**24" C-SERIES**  
*Wine Reserve*

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HC24WB-4-1L	HC24WB4F-00-SLS0W	Left	No
HC24WB-4-1R	HC24WB4F-00-SRS0W	Right	No
HC24WB-4-2L	HC24WB4F-00-PL00W	Left	No
HC24WB-4-2R	HC24WB4F-00-PR00W	Right	No
HC24WB-4-3L	HC24WB4F-00-TLS0W	Left	No
HC24WB-4-3R	HC24WB4F-00-TRS0W	Right	No
HC24WB-4-4L	HC24WB4F-00-RL00W	Left	No
HC24WB-4-4R	HC24WB4F-00-RR00W	Right	No
HC24WB-4-1LL	HC24WB4F-00-SLSLW	Left	Yes
HC24WB-4-1RL	HC24WB4F-00-SRSLW	Right	Yes
HC24WB-4-2LL	HC24WB4F-00-PL0LW	Left	Yes
HC24WB-4-2RL	HC24WB4F-00-PR0LW	Right	Yes
HC24WB-4-3LL	HC24WB4F-00-TLSLW	Left	Yes
HC24WB-4-3RL	HC24WB4F-00-TRSLW	Right	Yes
HC24WB-4-4LL	HC24WB4F-00-RL0LW	Left	Yes
HC24WB-4-4RL	HC24WB4F-00-RR0LW	Right	Yes



**24" C-SERIES**  
*Wine Reserve*

