

MANUAL LIGHTING PROCEDURE

In the unlikely event that your hot rod should ever fail, your Traeger grill can also be manually relit. Remove the porcelain grill (s), angled drip pan, and U-shaped firepot cover. Pour approximately 1/2 cup of TRAEGER BBQ PELLETS into the firepot. Overfilling the firepot with pellets will over heat the unit and/or cause incomplete combustion. When placing the pellets into the firepot make sure you get them in the firepot and not under the baffle pan. Squirt approximately 2 tablespoons of alcohol gel into the firepot on top of the pellets. Use a long fireplace match to light the alcohol gel. DO NOT TURN THE “ON” SWITCH ON YET! Wait approximately four minutes before turning the power switch “ON”. This will allow the pellets to combust and begin burning properly.

WARNING!

NEVER ATTEMPT TO SQUIRT ALCOHOL GEL INTO A FIRE THAT IS ALREADY BURNING OR INTO A HOT FIREPOT. THE ALCOHOL GEL BOTTLE COULD EXPLODE AND YOU COULD BE SERIOUSLY BURNED. IF YOU NEED TO “RE-LIGHT”, TURN YOUR GRILL OFF. WAIT UNTIL THE FIREPOT COOLS OFF COMPLETELY. MAKE SURE THERE ARE NO BURNING PELLETS IN THE BOTTOM OF THE FIREPOT BEFORE ATTEMPTING TO RE-LIGHT THE GRILL.